

**Description**

Fastener Length: 1/2", Thread: 10-32, Thread Length: 23/64", pan head, NAS1301 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                     |
|-------------------------|---------------------|
| SKU / Model:            | NAS1301C108         |
| Minimum Qty (MOQ):      | 20                  |
| NSN:                    | 5305-00-083-6645    |
| ECCN:                   | EAR99               |
| National Motor Freight: | 013680, Alum Screws |



# P/N NAS1301C10-8 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                    | 2a   |
| <b>Thread Direction:</b>                                | Right-hand   |
| <b>Thread Length:</b>                                   | 0.348 Inches Minimum And 0.360 Inches Maximum  |
| <b>Fastener Length:</b>                                 | 0.468 Inches Minimum And 0.500 Inches Maximum  |
| <b>Head Style:</b>                                      | Pan  |
| <b>Head Diameter:</b>                                   | 0.357 Inches Minimum And 0.373 Inches Maximum  |
| <b>Head Height:</b>                                     | 0.122 Inches Minimum And 0.132 Inches Maximum  |
| <b>Washer Quantity:</b>                                 | 2  |
| <b>Internal Drive Style:</b>                            | Cross Recess Type 1  |
| <b>Nominal Thread Diameter:</b>                         | 0.190 Inches   |
| <b>Thread Quantity Per Inch:</b>                        | 32   |
| <b>Secondary Washer Relationship To Primary Washer:</b> | Not Identical  |
| <b>Secondary Washer Style:</b>                          | Flat   |
| <b>Primary Washer Outside Diameter:</b>                 | 0.337 Inches Nominal   |
| <b>Secondary Washer Outside Diameter:</b>               | 0.338 Inches Minimum And 0.348 Inches Maximum  |
| <b>Primary Washer Style:</b>                            | Split Helical Ring   |
| <b>Primary Washer Material Thickness:</b>               | 0.047 Inches Minimum   |
| <b>Secondary Washer Material Thickness:</b>             | 0.029 Inches Minimum And 0.035 Inches Maximum  |
| <b>Material:</b>  | Steel Comp 301 Primary Washer Or Steel Comp 302 Primary Washer Or Steel Comp 304 Primary Washer Or Steel Comp 316 Primary Washer Or Steel Comp 347 Primary Washer Or Steel Comp 348 Primary Washer             |
| <b>Material:</b>  | Steel Comp 301 Secondary Washer Or Steel Comp 302 Secondary Washer Or Steel Comp 304 Secondary Washer Or Steel Comp 316 Secondary Washer Or Steel Comp 347 Secondary Washer Or Steel Comp 348 Secondary Washer |
| <b>Material:</b>  | Steel Comp 303 Fastener Or Steel Comp 303se Fastener   |
| <b>Material Document And Classification:</b>            | Mil-s-7720 Mil Spec 1st Material Response Fastener Or Astm A582 Assn Std 2nd Material Response Fastener  |
| <b>Surface Treatment:</b>                               | Passivate Fastener   |
| <b>Surface Treatment:</b>                               | Passivate Primary Washer   |
| <b>Surface Treatment:</b>                               | Passivate Secondary Washer   |
| <b>Thread Series Designator:</b>                        | Unf  |
| <b>Specification/standard Data:</b>                     | 80205-nas1301 Professional/industrial Association Standard   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/assembled+washer+screws/NAS1301C10-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.