

## Description

Fastener Length: 1/4", Thread: 4-40, Thread Length: 1/8", pan head, NAS1301 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1301C44
Minimum Qty (MOQ):	50
NSN:	5305-01-132-3387
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS1301C4-4 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.127 Inches Minimum
<b>Fastener Length:</b>	0.218 Inches Minimum And 0.250 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.205 Inches Minimum And 0.219 Inches Maximum
<b>Head Height:</b>	0.078 Inches Minimum And 0.080 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	55000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 430 Overall Or Steel Comp 303 Overall Or Steel Comp 303se Overall
<b>Material Document And Classification:</b>	Qq-s-763 Fed Spec 1st Material Response Overall Or Astm A582 Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unc
<b>Specification/standard Data:</b>	80205-nas1301 Professional/industrial Association Standard

## How to Order

Order this assembled washer screw from our inventory online by visiting <https://military-fasteners.com/screws/assembled+washer+screws/NAS1301C4-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.