

Description

NAS1301C6-5 Assembled Washer Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1301C65
Minimum Qty (MOQ):	50
NSN:	5305-01-023-6238
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1301C6-5 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.218 Inches Minimum
Fastener Length:	0.280 Inches Minimum And 0.312 Inches Maximum
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Washer Quantity:	2
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Secondary Washer Relationship To Primary Washer:	Not Identical
Secondary Washer Style:	Flat
Primary Washer Outside Diameter:	0.253 Inches Nominal
Secondary Washer Outside Diameter:	0.253 Inches Minimum And 0.263 Inches Maximum
Primary Washer Style:	Split Helical Ring
Primary Washer Material Thickness:	0.031 Inches Nominal
Secondary Washer Material Thickness:	0.013 Inches Minimum And 0.019 Inches Maximum
Material:	Steel Comp 430 Overall Or Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 301 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1301 Professional/industrial Association Standard

How to Order

Order this assembled washer screw from our inventory online by visiting <https://military-fasteners.com/screws/assembled+washer+screws/NAS1301C6-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.