

**Description**

NAS1301C6-5 Assembled Washer Screw

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1301C65
Minimum Qty (MOQ):	50
NSN:	5305-01-023-6238
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE  
AVAILABLE

## P/N NAS1301C6-5 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.218 Inches Minimum
<b>Fastener Length:</b>	0.280 Inches Minimum And 0.312 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.256 Inches Minimum And 0.270 Inches Maximum
<b>Head Height:</b>	0.087 Inches Minimum And 0.097 Inches Maximum
<b>Washer Quantity:</b>	2
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Secondary Washer Relationship To Primary Washer:</b>	Not Identical
<b>Secondary Washer Style:</b>	Flat
<b>Primary Washer Outside Diameter:</b>	0.253 Inches Nominal
<b>Secondary Washer Outside Diameter:</b>	0.253 Inches Minimum And 0.263 Inches Maximum
<b>Primary Washer Style:</b>	Split Helical Ring
<b>Primary Washer Material Thickness:</b>	0.031 Inches Nominal
<b>Secondary Washer Material Thickness:</b>	0.013 Inches Minimum And 0.019 Inches Maximum
<b>Material:</b>	Steel Comp 430 Overall Or Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 301 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall Or Steel Corrosion Resisting Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unc
<b>Specification/standard Data:</b>	80205-nas1301 Professional/industrial Association Standard

## How to Order

Order this assembled washer screw from our inventory online by visiting <https://military-fasteners.com/screws/assembled+washer+screws/NAS1301C6-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.