

P/N NAS1301C8-8

Description

Fastener Length: 15/32", Thread: 8-32, Thread Length: 23/64", NAS1301 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1301C88

Minimum Qty (MOQ): 25

NSN: 5305-01-051-8022

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1301C8-8 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.359 Inches Minimum
Fastener Length:	0.468 Inches Minimum And 0.500 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Washer Quantity:	2
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Secondary Washer Relationship To Primary Washer:	Not Identical
Secondary Washer Style:	Flat
Primary Washer Outside Diameter:	0.296 Inches Maximum
Secondary Washer Outside Diameter:	0.307 Inches Minimum And 0.317 Inches Maximum
Primary Washer Style:	Split Helical Ring
Primary Washer Material Thickness:	0.040 Inches Minimum
Secondary Washer Material Thickness:	0.013 Inches Minimum And 0.019 Inches Maximum
Material:	Steel Comp 430 Overall Or Steel Comp 303 Overall Or Steel Corrosion Resisting Overall Or Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 304 Overall Or Steel Comp 316 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1301 Professional/industrial Association Standard

How to Order

Order this assembled washer screw from our inventory online by visiting https://military-fasteners.com/screws/assembled+washer+screws/NAS1301C8-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.