



★ FASTENERS

Military-Fasteners.com

P/N NAS1303-1

Description

Fastener Length: 3/8", Thread: 10-32, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS13031 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5306-01-394-0832 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1303-1 Specifications

| | |
|----------------------------------|-------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.338 Inches Maximum |
| Fastener Length: | 0.400 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.173 Inches Maximum |
| Width Between Flats: | 0.376 Inches Maximum |
| Grip Diameter: | 0.190 Inches Maximum |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.072 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1303-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.