

Description

Fastener Length: 3/8", Thread: 10-32, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS13031
Minimum Qty (MOQ):	100
NSN:	5306-01-394-0832
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1303-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Maximum
Fastener Length:	0.400 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.173 Inches Maximum
Width Between Flats:	0.376 Inches Maximum
Grip Diameter:	0.190 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.072 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1303-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.