

P/N NAS1303-10H

Description

Fastener Length: 15/16", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS130310H

Minimum Qty (MOQ): 15 EA

NSN: 5306-00-952-5707

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)

NO IMAGE AVAILABLE

^{*} See page 2 for technical characteristics

P/N NAS1303-10H Specifications

Tread Length: 0.338 Inches Minimum Fastener Length: 0.963 Inches Nominal Head Style: Dished Hexagon Head Height: 0.110 Inches Nominal Width Between Flats: 0.367 Inches Minimum And 0.376 Inches Maximum Width Between Flats: 0.046 Inches Nominal Grip Diameter: 0.046 Inches Minimum And 0.1895 Inches Maximum Nominal Thread Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Nominal Thread Diameter: 0.625 Inches Nominal Hole Quantity: 3 Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Mil-s-5030 Mil Spec Material Document And Classification: 3rd Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Classification: Thread Series Designator: Unf	Thread Class:	3a
Fastener Length: 0.963 Inches Nominal Head Style: Dished Hexagon Head Height: 0.110 Inches Nominal Width Between Flats: 0.367 Inches Minimum And 0.376 Inches Maximum Hole Diameter: 0.046 Inches Nominal Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Nominal Thread Diameter: 0.190 Inches Grip Length: 0.625 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Material: Steed Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Mile-s-6036 Mil Spec 2nd Material Response Overall Or Mile-s-6039 Mil Spec 2nd Material Response Overall Or Mile-s-6049 Mil Spec 5th Material Response Overall Or Mile-s-6049 Mile Spec 5th Mate	Thread Direction:	Right-hand
Head Style: Dished Hexagon Head Height: 0.110 Inches Nominal Width Between Flats: 0.367 Inches Minimum And 0.376 Inches Maximum Hole Diameter: 0.0486 Inches Nominal Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Nominal Thread Diameter: 0.1990 Inches Grip Length: 0.625 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 32 Winimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Mil-s-5026 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mi	Thread Length:	0.338 Inches Minimum
Head Height: 0.110 Inches Nominal Width Between Flats: 0.367 Inches Minimum And 0.376 Inches Maximum Hole Diameter: 0.046 Inches Nominal Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Nominal Thread Diameter: 0.190 Inches Grip Length: 0.625 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 160000 Pounds Per Square Inch Hardness Rating: 160000 Pounds Per Square Inch Hexagon Corners Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: 0q-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Fastener Length:	0.963 Inches Nominal
Width Between Flats: 0.367 Inches Minimum And 0.376 Inches Maximum Hole Diameter: 0.046 Inches Nominal Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Nominal Thread Diameter: 0.190 Inches Grip Length: 0.625 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp Mili-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6094 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Unf	Head Style:	Dished Hexagon
Hole Diameter: 0.046 Inches Nominal Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Nominal Thread Diameter: 0.190 Inches Grip Length: 0.625 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Pr Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 1600000 Pounds Per Square Inch Hardness Rating: 160000 Pounds Per Square Inch Hardness Rating: 160000 Pounds Per Square Inch Hardness Rating: 1600000 Pounds Per Square Inch Hardness Rating: 16000000000000000000000000000000000000	Head Height:	0.110 Inches Nominal
Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Nominal Thread Diameter: 0.190 Inches Grip Length: 0.625 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th	Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Nominal Thread Diameter: Grip Length: O.625 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: Hardness Rating: Hole Configuration Style: Hexagon Corners Material: Material: Material Document And Classification: Surface Treatment Document And Classification: Thread Series Designator: Unf O.99 Inches O.625 Inches Nominal O.626 Inches Nominal	Hole Diameter:	0.046 Inches Nominal
Grip Length: 0.625 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8730 Overall Or Steel Comp 8740 Overall Mill-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec Material Response Overall Or Mil-s-6049 Mil Spec 5th Ma	Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Hole Quantity: Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: Hole Configuration Style: Hole Configuration Style: Hexagon Corners Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or M	Nominal Thread Diameter:	0.190 Inches
Hole Type: Drilled Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: Hole Configuration Style: Hexagon Corners Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec Material Document And Classification: Mini-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response	Grip Length:	0.625 Inches Nominal
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hexagon Corners Material: Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Hole Quantity:	3
Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hexagon Corners Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material 8urface Treatment: Cadmium Overall And Chromate Overall Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Hole Type:	Drilled
Hardness Rating: Hole Configuration Style: Hexagon Corners Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Respons	Thread Quantity Per Inch:	32
Hole Configuration Style: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8745 Overall Or Steel Comp 8745 Overall Or Steel Comp 8745 Overall Or Steel Comp 8740 Overall Or Steel Comp 8740 Overall Or Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unf	Hole Configuration Style:	Hexagon Corners
Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Classification: Thread Series Designator: 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5t	Material:	
Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall Unf Unf	Material Document And Classification:	3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material
Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas1303 Professional/industrial Association Standard	Thread Series Designator:	Unf
	Specification/standard Data:	80205-nas1303 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS1303-10H and selecting the quantity you want then click

