

P/N NAS1303-32D

Description

Fastener Length: 2-5/16", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS130332D

Minimum Qty (MOQ): 10 EA

NSN: 5306-00-969-6753

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1303-32D Specifications

Thread Class:	20
	3a
Thread Direction:	Right-hand
Thread Length:	0.338 Inches Minimum
Fastener Length:	2.338 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Nominal
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Nominal First Hole
Single Shear Strength:	96000 Pounds Per Square Inch
Nominal Thread Diameter:	0.190 Inches
Grip Length:	2.000 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.175 Inches Nominal First Hole
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1303 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS1303-32D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.