



Military-Fasteners.com

P/N NAS1303-5D

Description

Fastener Length: 43/64", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS13035D
Minimum Qty (MOQ):	20 EA
NSN:	5306-01-054-4598
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1303-5D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	0.642 Inches Minimum And 0.672 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	0.469 Inches Minimum First Hole And 0.519 Inches Maximum First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec Single Material Response Overall Or Ams 6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1303-5D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.