

P/N NAS1304-13H

Military-Fasteners.com

Description

Fastener Length: 1-1/4", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 7/16", drilled head

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

SKU / Model:	NAS130413H
Minimum Qty (MOQ):	10
NSN:	5306-00-834-8808
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1304-13H Specifications

Thread Direction:Right-handThread Length:0.400 Inches Minimum And 0.450 Inches MaximumFastener Length:1.222 Inches Minimum And 1.252 Inches MaximumHead Style:Dished HexagonHead Height:0.125 Inches NominalWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumHole Diameter:0.446 Inches NominalGrip Diameter:0.250 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesOrigi Length:0.802 Inches Minimum And 0.822 Inches MaximumHole Quantity:3Hole Type:DirilledThread Quantity Per Inch:28		
Thread Length:0.400 Inches Minimum And 0.450 Inches MaximumFastener Length:1.222 Inches Minimum And 1.252 Inches MaximumHead Style:Dished HexagonHead Height:0.125 Inches NominalWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumHole Diameter:0.046 Inches NominalGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.500 InchesOxfor Length:0.520 Inches Minimum And 0.822 Inches MaximumHole Quantity:3Hole Type:DifledDirilledSaleThread Quantity Per Inch:28	Thread Class:	3a
Fastener Length:1.222 Inches Minimum And 1.252 Inches MaximumHead Style:Dished HexagonHead Height:0.125 Inches NominalWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumHole Diameter:0.046 Inches NominalGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesOsto Inches0.802 Inches Minimum And 0.822 Inches MaximumHole Quantity:3Hole Type:DiriledThread Quantity Per Inch:28	Thread Direction:	Right-hand
Head Style:Dished HexagonHead Style:Dished HexagonHead Height:0.125 Inches NominalWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumHole Diameter:0.046 Inches NominalGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesGrip Length:0.802 Inches Minimum And 0.822 Inches MaximumHole Quantity:3Hole Type:DiriledDiriledDiriledState ComponentiesState ComponentiesBilled Rue Ritting Per Inch:State Componenties	Thread Length:	0.400 Inches Minimum And 0.450 Inches Maximum
Head Height:0.125 Inches NominalHead Height:0.430 Inches NominalWidth Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumHole Diameter:0.046 Inches NominalGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesO.802 Inches Minimum And 0.822 Inches MaximumHole Quantity:3Hole Type:DrilledDrilled28	Fastener Length:	1.222 Inches Minimum And 1.252 Inches Maximum
Width Between Flats:0.430 Inches Minimum And 0.439 Inches MaximumHole Diameter:0.046 Inches NominalGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 Inches0.802 Inches Minimum And 0.822 Inches MaximumHole Quantity:3Hole Type:DilledDilledDilledBet Type:28	Head Style:	Dished Hexagon
Hole Diameter:0.046 Inches NominalGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesGrip Length:0.802 Inches Minimum And 0.822 Inches MaximumHole Quantity:3Hole Type:DrilledDrilled28	Head Height:	0.125 Inches Nominal
Grip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesGrip Length:0.802 Inches Minimum And 0.822 Inches MaximumHole Quantity:3Hole Type:DilledDistrict Quantity Per Inch:28	Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Nominal Thread Diameter:0.250 InchesGrip Length:0.802 Inches Minimum And 0.822 Inches MaximumHole Quantity:3Hole Type:DriledDistribution:Distribution:Bole Quantity Per Inch:8	Hole Diameter:	0.046 Inches Nominal
Grip Length:0.802 Inches Minimum And 0.822 Inches MaximumHole Quantity:3Hole Type:DrilledDrilled28	Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Hole Quantity:3Hole Type:DrilledThread Quantity Per Inch:28	Nominal Thread Diameter:	0.250 Inches
Hole Type: Drilled Thread Quantity Per Inch: 28	Grip Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Thread Quantity Per Inch: 28	Hole Quantity:	3
	Hole Type:	Drilled
Minimum Tensile Strength: 160000 Pounds Per Square Inch	Thread Quantity Per Inch:	28
	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style: Hexagon Corners	Hole Configuration Style:	Hexagon Corners
Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Overall	Material:	
Material Document AndMil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rdClassification:Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall		
Surface Treatment: Cadmium Overall And Chromate Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:		Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unf	Thread Series Designator:	Unf
Specification/standard Data: 80205-nas1304 Professional/industrial Association Standard	Specification/standard Data:	80205-nas1304 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS1304-13H</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.