

P/N NAS1304-2H

Description

length: 0.550", thread: 1/4-28, hex head tension bolt, drilled head, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

NAS6604H2

SKU / Model: NAS13042H

Minimum Qty (MOQ): 20

NSN: 5306-01-339-5411

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS1304-2H Specifications

3a
Right-hand
0.425 Inches Minimum
0.550 Inches Nominal
Dished Hexagon
0.125 Inches Nominal
0.430 Inches Minimum And 0.439 Inches Maximum
0.046 Inches Minimum And 0.056 Inches Maximum
0.2485 Inches Minimum And 0.2495 Inches Maximum
96000 Pounds Per Square Inch
0.250 Inches
0.125 Inches Nominal
3
Drilled
28
160000 Pounds Per Square Inch
34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hexagon Corners
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material
Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Unf

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS1304-2H and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.