

P/N NAS1304-7H

Description

Fastener Length: 7/8", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS13047H

Minimum Qty (MOQ): 10 EA

NSN: 5306-00-680-6164

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1304-7H Specifications

3a
Right-hand
0.400 Inches Minimum And 0.450 Inches Maximum
0.848 Inches Minimum And 0.878 Inches Maximum
Dished Hexagon
0.125 Inches Nominal
0.430 Inches Minimum And 0.439 Inches Maximum
0.046 Inches Nominal
0.2485 Inches Minimum And 0.2495 Inches Maximum
96000 Pounds Per Square Inch
0.250 Inches
0.428 Inches Minimum And 0.448 Inches Maximum
3
Drilled
28
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hexagon Corners
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Unf

How to Order

