

# **P/N NAS1304-8DH**

## **Description**

Fastener Length: 59/64", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

### **Additional Information**

SKU / Model:	NAS13048DH
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-616-2759
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1304-8DH Specifications

hread Class:	3a
hread Direction:	Right-hand
hread Length:	0.425 Inches Minimum
astener Length:	0.925 Inches Nominal
lead Style:	Dished Hexagon
lead Height:	0.125 Inches Nominal
Vidth Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
lole Diameter:	0.046 Inches Nominal
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
hank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
ingle Shear Strength:	96000 Pounds Per Square Inch
Iominal Thread Diameter:	0.250 Inches
Grip Length:	0.500 Inches Nominal
lole Quantity:	3
lole Type:	Drilled
hread Quantity Per Inch:	28
linimum Tensile Strength:	160000 Pounds Per Square Inch
lardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
lole Configuration Style:	Hexagon Corners
Distance From Head Largest Bearing Gurface To Shank Hole Center:	0.747 Inches Nominal First Hole
daterial:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Naterial Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
urface Treatment:	Cadmium Overall And Chromate Overall
urface Treatment Document And lassification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
hread Series Designator:	Unf

# **How to Order** Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS1304-8DH">https://military-fasteners.com/bolts/shear+bolts/NAS1304-8DH</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.