

## P/N NAS1305-10

### **Description**

Fastener Length: 1-7/64", Thread: 1/4-24, Thread Length: 7/16

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS130510

Minimum Qty (MOQ): 20

NSN: 5306-00-816-0948

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1305-10 Specifications**

Thread Direction: Right-hand  Thread Length: 0.394 Inches Minimum And 0.444 Inches Maximum  Fastener Length: 1.079 Inches Minimum And 1.109 Inches Maximum  Head Style: Dished Hexagon  Head Height: 0.156 Inches Minimum And 0.171 Inches Maximum  Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum  Width Between Flats: 0.3110 Inches Minimum And 0.3120 Inches Maximum  Mominal Thread Diameter: 0.312 Inches  Grip Length: 0.615 Inches Minimum And 0.635 Inches Maximum  Thread Quantity Per Inch: 24  Minimum Tensile Strength: 160000 Pounds Per Square Inch  Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Surface Treatment: Cadmium Overall  Thread Series Designator: Unf		
Thread Length:  0.394 Inches Minimum And 0.444 Inches Maximum  Fastener Length:  1.079 Inches Minimum And 1.109 Inches Maximum  Dished Hexagon  Head Style:  0.156 Inches Minimum And 0.171 Inches Maximum  Width Between Flats:  0.492 Inches Minimum And 0.502 Inches Maximum  Width Between Flats:  0.3110 Inches Minimum And 0.3120 Inches Maximum  Nominal Thread Diameter:  0.312 Inches  Grip Length:  0.615 Inches Minimum And 0.635 Inches Maximum  Thread Quantity Per Inch:  44  Minimum Tensile Strength:  160000 Pounds Per Square Inch  Hardness Rating:  36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material:  Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And  Classification:  Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Surface Treatment:  Cadmium Overall  Thread Series Designator:  Unf	Thread Class:	3a
Fastener Length:  1.079 Inches Minimum And 1.109 Inches Maximum  Head Style:  Dished Hexagon  Head Height:  0.156 Inches Minimum And 0.171 Inches Maximum  Width Between Flats:  0.492 Inches Minimum And 0.502 Inches Maximum  Grip Diameter:  0.3110 Inches Minimum And 0.3120 Inches Maximum  Nominal Thread Diameter:  0.312 Inches  Grip Length:  0.615 Inches Minimum And 0.635 Inches Maximum  Thread Quantity Per Inch:  4  Minimum Tensile Strength:  160000 Pounds Per Square Inch  Hardness Rating:  36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material:  Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Classification:  Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Thread Series Designator:  Unf	Thread Direction:	Right-hand
Head Style: Dished Hexagon Head Height: Dished Hexagon Used Height: Dished Hexagon Used Head Height: Dished Hexagon Used Hexago	Thread Length:	0.394 Inches Minimum And 0.444 Inches Maximum
Head Height: 0.156 Inches Minimum And 0.171 Inches Maximum  Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum  Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum  Nominal Thread Diameter: 0.615 Inches Minimum And 0.635 Inches Maximum  Thread Quantity Per Inch: 24  Minimum Tensile Strength: 160000 Pounds Per Square Inch  Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Classification: Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Surface Treatment: Cadmium Overall  Thread Series Designator: Unf	Fastener Length:	1.079 Inches Minimum And 1.109 Inches Maximum
Width Between Flats:  0.492 Inches Minimum And 0.502 Inches Maximum  0.3110 Inches Minimum And 0.3120 Inches Maximum  Nominal Thread Diameter:  0.312 Inches  Grip Length:  0.615 Inches Minimum And 0.635 Inches Maximum  Thread Quantity Per Inch:  24  Minimum Tensile Strength:  160000 Pounds Per Square Inch  Hardness Rating:  36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material:  Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And  Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Classification:  Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Thread Series Designator:  Unf	Head Style:	Dished Hexagon
Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum  Nominal Thread Diameter: 0.312 Inches  Grip Length: 0.615 Inches Minimum And 0.635 Inches Maximum  Thread Quantity Per Inch: 24  Minimum Tensile Strength: 160000 Pounds Per Square Inch  Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Ov	Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Nominal Thread Diameter: 0.312 Inches  Grip Length: 0.615 Inches Minimum And 0.635 Inches Maximum  Thread Quantity Per Inch: 24  Minimum Tensile Strength: 160000 Pounds Per Square Inch  Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Classification: Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Surface Treatment: Cadmium Overall  Thread Series Designator: Unf	Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Length: 0.615 Inches Minimum And 0.635 Inches Maximum  Thread Quantity Per Inch: 24  Minimum Tensile Strength: 160000 Pounds Per Square Inch  Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Surface Treatment: Cadmium Overall  Thread Series Designator: Unf	Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Thread Quantity Per Inch:  Minimum Tensile Strength:  160000 Pounds Per Square Inch  160000 Pounds Per Square Inch  36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material:  Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And  Classification:  Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Cadmium Overall  Thread Series Designator:  Unf	Nominal Thread Diameter:	0.312 Inches
Minimum Tensile Strength: 160000 Pounds Per Square Inch  Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material  Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Surface Treatment: Cadmium Overall  Thread Series Designator: Unf	Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material  Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Surface Treatment: Cadmium Overall  Unf	Thread Quantity Per Inch:	24
Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  Material Document And Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Surface Treatment: Cadmium Overall  Thread Series Designator: Unf	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material Document And Classification:  Surface Treatment:  Thread Series Designator:  Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall  Cadmium Overall  Unf	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Cadmium Overall Thread Series Designator: Unf	Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Surface Treatment: Cadmium Overall Thread Series Designator: Unf	Material Document And	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material
Thread Series Designator: Unf	Classification:	Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
-	Surface Treatment:	Cadmium Overall
Specification/standard Data: 80205-nas1305 Professional/industrial Association Standard	Thread Series Designator:	Unf
	Specification/standard Data:	80205-nas1305 Professional/industrial Association Standard

## **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1305-10">https://military-fasteners.com/bolts/machine+bolts/NAS1305-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1305-10">https://military-fasteners.com/bolts/machine+bolts/NAS1305-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1305-10">https://military-fasteners.com/bolts/machine+bolts/NAS1305-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1305-10">https://military-fasteners.com/bolts/machine+bolts/NAS1305-10</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1305-10">https://military-fasteners.com/bolts/machine+bolts/NAS1305-10</a> and selecting the quantity you want <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1305-10">https://military-fasteners.com/bolts/machine+bolts/NAS1305-10</a> and selecting the quantity you want <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1305-10">https://military-fasteners.com/bolts/machine+bolts/NAS1305-10</a> and selecting the your cart you can check out <a href="https://military-fasteners.com/bolts/NAS1305-10">https://military-fasteners.com/bolts/NAS1305-10</a> and selecting the your cart your cart you can check out <a href="https://military-fasteners.com/bolts/NAS1305-10">https://military-fasteners.com/bolts/NAS1305-10</a> and selecting the your cart your