

P/N NAS1305-11D

Description

Fastener Length: 1-5/32", Thread: 1/4-24, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS130511D

Minimum Qty (MOQ): 10 EA

NSN: 5306-00-944-2661

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1305-11D Specifications

Thread Direction: Right-hand Thread Length: 0.469 Inches Minimum Fastener Length: 1.157 Inches Nominal Head Style: Dished Hexagon Head Height: 0.156 Inches Nominal Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Nominal Thread Diameter: 0.312 Inches Nominal First Hole Nominal Thread Diameter: 0.688 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Miles-6526 Mil Spec 1st Material Response Overall Or Miles-6009 Mil Spec 2nd Material Response Overall Or Miles-6009 Mil Spec 3rd Material Document And Classification: Coverall Surface Treatment: Cadmium Overall And Chromate Overall Classification: Qe-p-416.ty 2 Cl 2 Fed Spec Single Treatment Response Overall Classification:	Thread Class:	3a
Thread Length: 0.469 Inches Minimum Fastener Length: 1.157 Inches Nominal Head Style: Dished Hexagon Midth Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.312 Inches Grip Length: 0.688 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches Grip Length: 0.688 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 45eel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material: 45eel Comp 4140 Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: 40ep-416.ty 2 Cl 2 Fed Spec Single Treatment Response Overall Oq-9-416.ty 2 Cl 2 Fed Spec Single Treatment Response Overall		
Fastener Length: 1.157 Inches Nominal Head Style: Dished Hexagon Head Height: 0.156 Inches Nominal Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.312 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches Nominal First Hole Nominal Thread Plameter: 0.388 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Malterial Document And Classification: Mili-s-5626 Mil Spec 1st Material Response Overall Or Mili-s-6098 Mil Spec 4th Material Response Overall Or Mili-s-6049 Mil Spec 5th Material Response Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Q-p-416,ty 2 C12 Fed Spec Single Treatment Response Overall		
Head Style: Dished Hexagon Head Height: 0.156 Inches Nominal Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.312 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches Grip Length: 0.688 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 0.6.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 5teel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Mater	Thread Length:	0.469 Inches Minimum
Head Height: 0.156 Inches Nominal Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.312 Inches Nominal Thread Diameter: 0.312 Inches Grip Length: 0.688 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Document And Classification: Variable Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Fastener Length:	1.157 Inches Nominal
Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum 0.3110 Inches Minimum And 0.3120 Inches Maximum 0.076 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches Grip Length: 0.688 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 0.976 Inches Nominal First Hole Distance From Head Largest Bearing Surface To Shank Hole Center: Material: 0.976 Inches Nominal First Hole Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Oq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Head Style:	Dished Hexagon
Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum 0.076 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches 0.321 Inches 0.688 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 0.976 Inches Nominal First Hole 0.976 Inches Nominal First Hole Steel Comp 4140 Overall And 40.0 Rockwell C Maximum Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material: Material Document And Classification: Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Oq-p-416.ty 2 Cl 2 Fed Spec Single Treatment Response Overall Oq-p-416.ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Head Height:	0.156 Inches Nominal
Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches Grip Length: 0.688 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 45cel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Miles-5626 Mil Spec 1st Material Response Overall Or Miles-5000 Mil Spec 2nd Material Response Overall Or Miles-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Grassification: 40q-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Nominal Thread Diameter: 0.312 Inches Grip Length: 0.688 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Grip Length: O.688 Inches Nominal Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Material: Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 5teel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material: 6teel Comp 4140 Overall Or Steel Comp E4340 Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: 6teratment Document And Classification: 7teratment Document And Classification: 7teratment Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Materia	Nominal Thread Diameter:	0.312 Inches
Minimum Tensile Strength: Hardness Rating: Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Material Document And Classification: Stufface Treatment: Cadmium Overall And Chromate Overall Oq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall Ocerall 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Operall O.976 Inches Nominal First Hole Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 8740 Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec	Grip Length:	0.688 Inches Nominal
Hardness Rating: Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Material Document And Classification: Material Document And Classification: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall 0.976 Inches Nominal First Hole Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	24
Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Og-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall Og-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material: Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Document And Classification: Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Cadmium Overall And Chromate Overall Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Distance From Head Largest Bearing Surface To Shank Hole Center:	0.976 Inches Nominal First Hole
Material Document And Classification: Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment Document And Classification: Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overal	Material:	
Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Material Document And Classification:	Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response
Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unf	Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
	Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS1305-11D and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.