

P/N NAS1305-21H

Description

Fastener Length: 1-3/4", Hole Diameter: 1/16", Thread: 1/4-24, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS130521H

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-690-5590

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1305-21H Specifications

ad Direction:	
ia Directioni	Right-hand
nd Length:	0.469 Inches Minimum
ener Length:	1.781 Inches Nominal
Style:	Dished Hexagon
Height:	0.156 Inches Nominal
n Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Diameter:	0.070 Inches Nominal
Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
nal Thread Diameter:	0.312 Inches
Length: 1	1.312 Inches Nominal
Quantity:	3
Type:	Drilled
nd Quantity Per Inch:	24
num Tensile Strength:	160000 Pounds Per Square Inch
ness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Configuration Style:	Hexagon Corners
rial:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
rial Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
ce Treatment:	Cadmium Overall And Chromate Overall
ce Treatment Document And ification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
ad Series Designator:	Unf
fication/standard Data:	80205-nas1305 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS1305-21H and selecting the quantity you want then click

