

P/N NAS1305-24DH

Description

Fastener Length: 1-31/32", Hole Diameter: 1/16", Thread: 1/4-24, Thread Length: 15/32", NAS1305 series bolt

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS130524DH

Minimum Qty (MOQ): 5

NSN: 5306-00-920-0697

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N NAS1305-24DH Specifications

Thread Direction: Right-hand Thread Length: 0.469 Inches Minimum Fastener Length: 1.969 Inches Nominal Head Style: Dished Hexagon Head Height: 0.156 Inches Nominal Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Hole Diameter: 0.070 Inches Nominal Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Hole Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.312 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.312 Inches Grip Length: 1.500 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches Grip Length: 1.500 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Distance From Head Largest Bearing Unitation Style: Hexagon Corners Material: Seel Comp 4.140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp Material Document And Classification: 27 Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response	Thread Class:	3a
Thread Length: 0.469 Inches Minimum Fastener Length: 1,969 Inches Nominal Head Style: 0.156 Inches Nominal Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Hole Diameter: 0.070 Inches Nominal Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.316 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.312 Inches Grip Length: 1.500 Inches Nominal First Hole Nomlnal Thread Diameter: 0.312 Inches Grip Length: 1.500 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Distance From Head Largest Bearing Surface To Shank Hole Center: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Mil-s-5030 Mill Spec 2nd Material Response Overall Or Mil-s-5030 Mill Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material R		
Fastener Length: 1.969 Inches Nominal Head Style: Dished Hexagon Head Height: 0.156 Inches Nominal Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Hole Diameter: 0.070 Inches Nominal Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Dlameter: 0.076 Inches Nominal First Hole Nominal Thread Dlameter: 0.312 Inches Grip Length: 1.500 Inches Nominal Hole Quantity: 3 Hole Type: Diffled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Distance From Head Largest Bearing Surface To Shank Hole Center: 1.788 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: 3740 Averall 3740 Averall Overall Or Miles-6098 Mil Spec 4th Material Response Overall Or Miles-6098 Mil Spec 4th Material Response Overall Or Miles-6098 Mil Spe		
Head Style: Dished Hexagon Head Height: 0.156 Inches Nominal Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Hole Diameter: 0.070 Inches Nominal Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches Grip Length: 1.500 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Distance From Head Largest Bearing Surface To Shank Hole Center: 1.788 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6099 Mil Spec 2nd Material Response Overall Or Mil-s-6099 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Respon	-	
Head Height: 0.156 Inches Nominal Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Hole Diameter: 0.070 Inches Nominal Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.312 Inches Nominal Thread Diameter: 0.312 Inches Grip Length: 1.500 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Distance From Head Largest Bearing surface To Shank Hole Center: 1.788 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Mil-s-6903 Mil Spec 3rd Material Response Overall Or Mil-s-6090 Mil Spec 2nd Material Response Overall Or Mil-s-6090 Mil Spec 2nd Material Response Overall Or Mil-s-6099 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec Sth Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec Sth Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec Sth Material Response Overall Or Mil-s-	_	
Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Hole Diameter: 0.070 Inches Nominal Grip Dameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches Grip Length: 1.500 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Distance From Head Largest Bearing Surface To Shank Hole Center: 1.788 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 8740 Overall Or Mil-s-6026 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 4	•	
Hole Diameter: 0.070 Inches Nominal Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches Grip Length: 1.500 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 160000 Pounds Per Square Inch Hole Configuration Style: Hexagon Corners Distance From Head Largest Bearing Surface To Shank Hole Center: 21,788 Inches Nominal First Hole Material: 51,880 And Classification: 52,626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: 21,72 Cl 3 Fed Spec All Treatment Responses Overall Classification: 0.076 Inches Nominal First Hole Surface Treatment Document And Classification: 0.076 Jed Comp Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Or Mil-s-		
Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches Grip Length: 1.500 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Mainimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Distance From Head Largest Bearing Surface To Shank Hole Center: 1.788 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mili-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5009 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec		
Shank Unthreaded Hole Diameter: 0.076 Inches Nominal First Hole Nominal Thread Diameter: 0.312 Inches Grip Length: 1.500 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Distance From Head Largest Bearing Surface To Shank Hole Center: 1.788 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mili-s-5626 Mil Spec 1st Material Response Overall Or Mili-s-6098 Mil Spec 2nd Material Response Overall Or Mili-s-6049 Mil Spec 5th Material Response Overall Or Mili-s-6098 Mil Spec 4th Material Response Overall Or Mili-s-6049 Mil Spec 5th Material Response Overall Or Mili-s-6049 Mil Spec 4th Material Response Overall Or Mili-s-6049 Mil Spec 4th Material Response Overall Or Mili-s-6049 Mil Spec 5th Material Response Overall Or Mili-s-6049 Mil Spec 4th Material Response Overall Or Mili-s-6049 Mil Spec 4th Material Response Overall Or Mili-s-6049 Mil Spec 4th Material Response Overall Or Mili-s-6049 Mili Spec 4th Material Response Overall Or Mili-s-6049 Mili Spec 4th Material Response Overall Or Mili-s-6049 Mili Spec 4th Material Response Overall Or Mi		
Nominal Thread Diameter: Grip Length: 1.500 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: Aliminum Tensile Strength: Hole Oungration Style: Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Material: Material Document And Classification: Nominal Thread Quantity 1.78 Inches Nominal First Hole Surface Treatment Document And Classification: Oq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification: Distance From Head Largest Bearing Steel Comp 4140 Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5t	•	
Grip Length: 1.500 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Distance From Head Largest Bearing Surface To Shank Hole Center: 1.788 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Respons		
Hole Quantity: Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: Hole Configuration Style: Hexagon Corners Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall Classification: Distance From Head Largest Bearing Surface Treatment: Cadmium Overall And Chromate Overall All-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec Response Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall		0.312 Inches
Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Distance From Head Largest Bearing Surface To Shank Hole Center: 1.788 Inches Nominal First Hole Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material R		
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hexagon Corners Distance From Head Largest Bearing Surface To Shank Hole Center: 1.788 Inches Nominal First Hole Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8740 Overall Or Steel Comp Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: 24 Minum Overall And Chromate Overall Cadmium Overall And Chromate Overall Cadmium Overall And Chromate Overall Classification:	Hole Quantity:	3
Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Oq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall	Hole Type:	Drilled
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Distance From Head Largest Bearing Surface To Shank Hole Center: 1.788 Inches Nominal First Hole Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Ove	Thread Quantity Per Inch:	24
Hole Configuration Style: Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface To Shank Hole Center: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 8740 Overall Or Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Respon	Hole Configuration Style:	Hexagon Corners
Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall		1.788 Inches Nominal First Hole
Material Document And Classification: 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall	Material:	
Surface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall	Material Document And Classification:	3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material
Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unjf		Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
	Thread Series Designator:	Unjf

How to Order
Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS1305-24DH and selecting the quantity you wan then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS1305-24DH and selecting the quantity you wanted the cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS1305-24DH and selecting the quantity you wanted the cart.
Duracid and have Military and Santana and
Provided by Military-Fasteners.com