

Description

Fastener Length: 2-23/64", Thread: 1/4-24, Thread Length: 31/64", NAS1305 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS130530D |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5306-00-052-6322 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1305-30D Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.444 Inches Minimum And 0.494 Inches Maximum |
| Fastener Length: | 2.329 Inches Minimum And 2.359 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.156 Inches Minimum And 0.181 Inches Maximum |
| Width Between Flats: | 0.409 Inches Minimum And 0.502 Inches Maximum |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 1.865 Inches Minimum And 1.885 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 2.138 Inches Minimum First Hole And 2.188 Inches Maximum First Hole |
| Material: | Steel Comp 4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2 Cl2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1305 Professional/industrial Association Standard |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1305-30D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.