

P/N NAS1305-32

Description

Fastener Length: 2-31/64", Thread: 1/4-24, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS130532

Minimum Qty (MOQ): 20 EA

NSN: 5306-00-577-5455

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1305-32 Specifications

3a
Right-hand
0.444 Inches Minimum And 0.494 Inches Maximum
2.454 Inches Minimum And 2.484 Inches Maximum
Dished Hexagon
0.156 Inches Minimum And 0.171 Inches Maximum
0.492 Inches Minimum And 0.502 Inches Maximum
0.3110 Inches Minimum And 0.3120 Inches Maximum
0.312 Inches
1.990 Inches Minimum And 2.010 Inches Maximum
24
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,ty2 Cl2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas1305 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS1305-32 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS1305-32 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS1305-32 and selecting the quantity you want then click