

## P/N NAS1305-32H

### **Description**

Fastener Length: 2-15/32", Hole Diameter: 1/16", Thread: 1/4-24, Thread Length: 15/32"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS130532H

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-997-7036

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1305-32H Specifications

3a
Right-hand
0.469 Inches Minimum
2.469 Inches Nominal
Dished Hexagon
0.156 Inches Nominal
0.492 Inches Minimum And 0.502 Inches Maximum
0.070 Inches Nominal
0.3110 Inches Minimum And 0.3120 Inches Maximum
96000 Pounds Per Square Inch
0.312 Inches
2.000 Inches Nominal
3
Drilled
24
160000 Pounds Per Square Inch
34.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hexagon Corners
Navy Special Project
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,ty2 Cl2 Fed Spec Single Treatment Response Overall
Unf

## **How to Order**

