

## P/N NAS1305-36

## **Description**

Fastener Length: 2-23/32", Thread: 5/16"-24, Thread Length: 15/32

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS130536

Minimum Qty (MOQ): 10


NSN: 5306-00-810-6232

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1305-36 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.469 Inches Minimum
Fastener Length:	2.719 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Nominal
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	2.250 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	29.0 Rockwell C Minimum Overall And 36.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1305 Professional/industrial Association Standard

## **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1305-36">https://military-fasteners.com/bolts/machine+bolts/NAS1305-36</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1305-36">https://military-fasteners.com/bolts/machine+bolts/NAS1305-36</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1305-36">https://military-fasteners.com/bolts/machine+bolts/NAS1305-36</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1305-36">https://military-fasteners.com/bolts/machine+bolts/NAS1305-36</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1305-36">https://military-fasteners.com/bolts/machine+bolts/NAS1305-36</a> and selecting the quantity you want the property of the proper