



★ FASTENERS

Military-Fasteners.com

P/N NAS1305-50D

## Description

Fastener Length: 3-39/64", Thread: 1/4-24, Thread Length: 31/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS130550D                                |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5306-01-263-9144                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1305-50D Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.444 Inches Minimum And 0.494 Inches Maximum                       |
| <b>Fastener Length:</b>                               | 3.479 Inches Minimum And 3.609 Inches Maximum                       |
| <b>Head Style:</b>                                    | Hexagon   |
| <b>Head Height:</b>                                   | 0.156 Inches Minimum And 0.171 Inches Maximum                       |
| <b>Width Between Flats:</b>                           | 0.492 Inches Minimum And 0.502 Inches Maximum                       |
| <b>Grip Diameter:</b>                                 | 0.3110 Inches Minimum And 0.3120 Inches Maximum                     |
| <b>Nominal Thread Diameter:</b>                       | 0.312 Inches  |
| <b>Grip Length:</b>                                   | 3.115 Inches Minimum And 3.135 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                               | 32.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| <b>Material:</b>                                      | Steel Comp 4140 Overall   |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall       |
| <b>Thread Series Designator:</b>                      | Unjf  |
| <b>Specification/standard Data:</b>                   | 80205-nas1305-50d Professional/industrial Association Standard      |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1305-50D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.