

P/N NAS1306-14

Description

Fastener Length: 1-29/64", Thread: 3/8-24, Thread Length: 9/16

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS130614

Minimum Qty (MOQ):

NSN: 5306-01-459-0868

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1306-14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.578 Inches Minimum
Fastener Length:	1.438 Inches Minimum And 1.468 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Nominal
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall And Steel Comp E4340 Overall And Steel Comp 6150 Overall And Steel Comp 8735 Overall And Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall And Mil-s-5000 Mil Spec 2nd Material Response Overall And Mil-s-8503 Mil Spec 3rd Material Response Overall And Mil-s-6098 Mil Spec 4th Material Response Overall And Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1306 Professional/industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS1306-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS1306-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS1306-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS1306-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/naseners.com/bolts/nase