

P/N NAS1306-14H

Description

Fastener Length: 1-7/16", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 9/16

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: NAS130614H

Minimum Qty (MOQ): 5

NSN: 5306-00-819-0640

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1306-14H Specifications

Thread Direction: Right-hand Thread Length: 0.578 Inches Minimum Fastener Length: 1.453 Inches Nominal Head Style: Dished Hexagon Head Height: 0.188 Inches Nominal Width Between Flats: 0.553 Inches Minimum And 0.564 Inches Maximum Hole Diameter: 0.070 Inches Nominal Grip Diameter: 0.3735 Inches Minimum And 0.3745 Inches Maximum Nominal Thread Diameter: 0.375 Inches Mominal Hole Quantity: 3 Hole Type: Drilled Hole Quantity: 3 Hole Type: Drilled Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall Hexagon Corners Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8736 Overall Material Document And Classification: Milis-s5626 Mill Spec 1st Material Response Overall Or Milis-5000 Mil Spec 2nd Material Response Overall Or Milis-s603 Mil Spec Streament: Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Cadmium Overall And Chromate Overall	Thread Class:	3a
Fastener Length: 1.453 Inches Nominal Head Style: Dished Hexagon Head Height: 0.188 Inches Nominal Width Between Flats: 0.553 Inches Minimum And 0.564 Inches Maximum Hole Diameter: 0.070 Inches Nominal Grip Diameter: 0.3735 Inches Minimum And 0.3745 Inches Maximum Nominal Thread Diameter: 0.375 Inches Grip Length: 0.875 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 4 Hardness Rating: 16.000 Pounds Per Square Inch Hole Configuration Style: Hexagon Corners Material: Seel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp B740 Overall Material Document And Classification: 3rd Auterial Response Overall Or Mili-s-6098 Mil Spec 2nd Material Response Overall Or Mili-s-6049 Mil Spec 5th Material Response Overall Or Mili-s-6098 Mil Spec 4th Material Response Overall Or Mili-s-6049 Mil Spec 5th Material Response Overall Or Mili-s-6098 Mil Spec 4th Material Response Overall Or Mili-s-6049 Mil Spec 5th Material Response Overall Or Mili-s-6098 Mil Spec 4th Material Response Overall Or Mili-s-6049 Mil Spec 5th Material Response Overall Or Mili-s-6049 Mil Spec 4th Material Response Overall Or Mili-s-6049 Mil Spec 4th Material Response Overall Or Mili-s-6049 Mil Spec	Thread Direction:	
Head Style: Dished Hexagon Head Height: 0.188 Inches Nominal Width Between Flats: 0.553 Inches Minimum And 0.564 Inches Maximum Hole Diameter: 0.070 Inches Nominal Grip Diameter: 0.3735 Inches Minimum And 0.3745 Inches Maximum Nominal Thread Diameter: 0.375 Inches Mominal Grip Length: 0.875 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 2 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Respo	Thread Length:	0.578 Inches Minimum
Head Height: 0.188 Inches Nominal Width Between Flats: 0.553 Inches Minimum And 0.564 Inches Maximum Hole Diameter: 0.070 Inches Nominal Grip Diameter: 0.3755 Inches Minimum And 0.3745 Inches Maximum Nominal Thread Diameter: 0.375 Inches Minimum And 0.3745 Inches Maximum Nominal Thread Diameter: 0.375 Inches Nominal Hole Quantity: 3 Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8736 Overall Or Mil-s-6028 Mil Spec 2nd Material Response Overall Or Mil-s-803 Mil Spec Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec Sth Material Response Overall Or Mil-s-6049 Mil Spec St	Fastener Length:	1.453 Inches Nominal
Width Between Flats: 0.553 Inches Minimum And 0.564 Inches Maximum Hole Diameter: 0.070 Inches Nominal Grip Diameter: 0.3735 Inches Minimum And 0.3745 Inches Maximum Nominal Thread Diameter: 0.375 Inches Grip Length: 0.875 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Mil-s-6024 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Or	Head Style:	Dished Hexagon
Hole Diameter: 0.070 Inches Nominal Grip Diameter: 0.3735 Inches Minimum And 0.3745 Inches Maximum Nominal Thread Diameter: 0.375 Inches Grip Length: 0.875 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Head Height:	0.188 Inches Nominal
Grip Diameter: 0.3735 Inches Minimum And 0.3745 Inches Maximum Nominal Thread Diameter: 0.375 Inches Grip Length: 0.875 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Ove	Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Nominal Thread Diameter: 0.375 Inches Grip Length: 0.875 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mili-s-5626 Mil Spec 1st Material Response Overall Or Mili-s-5000 Mil Spec 2nd Material Response Overall Or Mili-s-8503 Mil Spec Ath Material Response Overall Or Mili-s-6049 Mil Spec 5th Material Response Overall Or Mili-s-6049 Mili Spec	Hole Diameter:	0.070 Inches Nominal
Grip Length: 0.875 Inches Nominal Hole Quantity: 3 Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Srd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mi	Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Hole Quantity: Hole Type: Drilled Thread Quantity Per Inch: Minimum Tensile Strength: Hole Configuration Style: Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Cassification: Thread Series Designator: Unf Drilled Drilled Drilled Drilled 24 Milomum Tensile Strength: 160000 Pounds Per Square Inch Hexagon Corners Steel Comp 4140 Overall And 40.0 Rockwell C Maximum Overall Hexagon Corners Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Mil-s-6040 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th	Nominal Thread Diameter:	0.375 Inches
Hole Type: Drilled Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 8740 Overall Or Mil-s-5020 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec Material Document And Classification: Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 M	Grip Length:	0.875 Inches Nominal
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hexagon Corners Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unf	Hole Quantity:	3
Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Hole Configuration Style: Hexagon Corners Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5t	Hole Type:	Drilled
Hardness Rating: Hole Configuration Style: Material: Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unf	Thread Quantity Per Inch:	24
Hole Configuration Style: Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 8740 Overall Or Steel Comp 8740 Overall Or Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil S	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil	Hole Configuration Style:	Hexagon Corners
Material Document And Classification:3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response O	Material:	
Surface Treatment Document And Classification: Thread Series Designator: Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response Overall Unf	Material Document And Classification:	3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material
Classification: Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Surface Treatment:	Cadmium Overall And Chromate Overall
		Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas1306 Professional/industrial Association Standard	Thread Series Designator:	Unf
	Specification/standard Data:	80205-nas1306 Professional/industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS1306-14H and selecting the quantity you want

