

# P/N NAS1306-19DH

## **Description**

Fastener Length: 1-25/32", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 19/32"

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

### **Additional Information**

SKU / Model: NAS130619DH
Minimum Qty (MOQ): 1 EA

NSN: 5306-00-851-5171

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1306-19DH Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.553 Inches Minimum And 0.603 Inches Maximum
Fastener Length:	1.751 Inches Minimum And 1.781 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Nominal
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Nominal First Hole
Single Shear Strength:	96000 Pounds Per Square Inch
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.178 Inches Minimum And 1.198 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Corners
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.554 Inches Minimum First Hole And 1.584 Inches Maximum First Hole
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

# **How to Order** Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1306-19DH">https://military-fasteners.com/bolts/machine+bolts/NAS1306-19DH</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.