

P/N NAS1306-3

Military-Fasteners.com

Description

Fastener Length: 25/32", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 41/64

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

| SKU / Model: | NAS13063 |
|-------------------------|---|
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-811-0053 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS1306-3 Specifications

| Intead Direction:JacThread Direction:Right-handThread Length:0.603 Inches Minimum And 0.653 Inches MaximumFastear Length:0.751 Inches Minimum And 0.781 Inches MaximumHead Style:Dished HexagonHead Height:0.186 Inches NominalWidth Between Flats:0.553 Inches Minimum And 0.576 Inches MaximumHole Diameter:0.070 Inches NominalOnto Inches Nominal0.757 InchesOminal Thread Diameter:0.375 Inches Minimum And 0.3745 Inches MaximumNominal Thread Diameter:0.375 Inches Minimum And 0.3745 Inches MaximumOminal Thread Diameter:0.375 Inches Minimum And 0.198 Inches MaximumHole Quantity:0.375 Inches Minimum And 0.198 Inches MaximumHole Quantity:0.376 Inches Minimum And 0.198 Inches MaximumHole Type:DirlledHole Type:DirlledHole Type:10000 Pounds Per Square InchHole Configuration Style:Hexagon CorrersMaterial:Steel Comp 4140 Overall On Steel Comp E4340 Overall On Steel Com | Thread Class: | 3a |
|---|------------------------------|---|
| Thread Length:0.603 Inches Minimum And 0.653 Inches MaximumFastener Length:0.751 Inches Minimum And 0.781 Inches MaximumHead Style:Dished HeagonHead Height:0.188 Inches NominalWidth Between Flats:0.553 Inches Minimum And 0.564 Inches MaximumHole Diameter:0.070 Inches NominalGrip Diameter:0.3735 Inches Minimum And 0.1745 Inches MaximumOnto Inches Nominal0.375 Inches Minimum And 0.1745 Inches MaximumHole Diameter:0.375 Inches Minimum And 0.198 Inches MaximumGrip Length:0.375 Inches Minimum And 0.198 Inches MaximumHole Quantity:0.315 Inches Minimum And 0.198 Inches MaximumHole Output:0.400 Inthes Minimum And 0.198 Inches MaximumHole Output:0.560 Rockwell CMINIMUM And 0.198 Inches Maximum OverallHole Output:0.560 Rockwell CMINIMUM And 0.080 Rockwell CMINIMUM OverallHardness Rating:0.560 Rockwell CMINIMUM Overall And 4.0.8 Rockwell CMaximum OverallHore Output:8.560 Rockwell CMINIMUM Overall And 4.0.8 Rockwell CMaximum Overall On Steel Comp B735 Overall Or Mil-s-6503 Mil Spec 3rdMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 2rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6039 Mil Spec 3rdStrates Treatment:Garium Overall And Chromate OverallSurface Treatment:< | | |
| Fastener Length:0.751 Inches Minimum And 0.781 Inches MaximumHead Style:Dished HexagonHead Height:0.188 Inches NominalHead Height:0.188 Inches NominalWidth Between Flats:0.553 Inches Minimum And 0.564 Inches MaximumHole Diameter:0.707 Inches NominalGrip Diameter:0.3735 Inches Minimum And 0.3745 Inches MaximumNominal Thread Diameter:0.375 Inches Minimum And 0.3745 Inches MaximumNominal Thread Diameter:0.375 Inches Minimum And 0.198 Inches MaximumHole Oguantity:3Hole Type:Diledches Maximum And 0.198 Inches MaximumHole Type:Diledches Maximum And 0.198 Inches MaximumHole Oguantity:3Hole Oguantity:6.0000 Pounds Per Square InchHardness Rating:6.0000 Pounds Per Square InchHole Configuration Style:Hexagon CornersMaterial Rocument And Classification:Steel Comp 4140 Oxetal Or Steel Comp E340 Oxerall Or Steel Comp E350 Oxerall Or Mil-s-6009 Mil Spec 2nd Material Response Overall Or Mil-s-6009 Mil Spec 3th Material Response Overall Or Mil-s-6009 Mil Spec 2th Material Response Overall Or Mil-s-6009 M | | |
| Head Style:Dished HexagonHead Height:0.188 Inches NominalWidth Between Flats:0.553 Inches Minimum And 0.564 Inches MaximumHole Diameter:0.070 Inches NominalGrip Diameter:0.373 Inches Minimum And 0.3745 Inches MaximumMominal Thread Diameter:0.375 InchesGrip Length:0.375 Inches Minimum And 0.198 Inches MaximumHole Quantity:3Hole Quantity:3Hole Quantity:10000 Pounds Per Square InchHole Quantity:160000 Pounds Per Square InchHole Configuration Style:160000 Pounds Per Square InchHole Configuration Style:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp E4340 Overall Or Steel Comp E4340 Overall Or Mil-s-6049 Mil Spec Sth Material Response Overall Or Mil-s-6049 Mil Spec Sth | Thread Length: | 0.603 Inches Minimum And 0.653 Inches Maximum |
| Head Height:0.188 Inches NominalWidth Between Flats:0.553 Inches Minimum And 0.564 Inches MaximumHole Diameter:0.070 Inches NominalGrip Diameter:0.3735 Inches Minimum And 0.3745 Inches MaximumNominal Thread Diameter:0.3735 Inches0.3755 Inches0.3735 Inches Minimum And 0.198 Inches MaximumNominal Thread Diameter:0.375 Inches0.178 Inches Minimum And 0.198 Inches MaximumHole Quantity:311Hole Type:DrilledHole Type:Drilled1160000 Pounds Per Square InchHardenss Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersMaterial Document And Classification:Nils-S626 Mil Spec 1st Material Response Overall Or Mils-S000 Mil Spec 2nd Material Response Overall Or Mils-S608 Mil Spec 4th Material Response Overall Or Mils-S6049 Mil Spec 3th Material Response Overall Or Mils-S608 Mil Spec 4th Material Response Overall Or Mils-S6049 Mil Spec 3th Material Response Overall Or Mils-S608 Mil Spec 4th Material Response Overall Or Mils-S6049 Mil Spec 3th Material Response Overall Or Mils-S604 | Fastener Length: | 0.751 Inches Minimum And 0.781 Inches Maximum |
| Width Between Flats:0.553 Inches Minimum And 0.564 Inches MaximumHole Diameter:0.070 Inches NominalGrip Diameter:0.3735 Inches Minimum And 0.3745 Inches MaximumNominal Thread Diameter:0.375 Inches0.375 Inches0.375 InchesGrip Length:0.375 Inches Minimum And 0.198 Inches MaximumHole Quantity:3Hole Type:DilledThread Quantity Per Inch:24000 Pounds Per Square Inch10000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersMaterial Document And Classification:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallSurface Treatment:Cadmium Overall Or Mil-s-6098 Mil Spec 2th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil | Head Style: | Dished Hexagon |
| Hole Diameter:0.070 Inches NominalGrip Diameter:0.3735 Inches Minimum And 0.3745 Inches MaximumNominal Thread Diameter:0.375 InchesGrip Length:0.178 Inches Minimum And 0.198 Inches MaximumHole Quantity:3Hole Quantity:0.178 Inches Minimum And 0.198 Inches MaximumHole Quantity:3Hole Type:prilledThread Quantity Per Inch:24Adoou Pounds Per Square Inch36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersHole Configuration Style:Exel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Scafe Mis Spec 1st Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Respo | Head Height: | 0.188 Inches Nominal |
| Grip Dameter:0.3735 Inches Minimum And 0.3745 Inches MaximumNominal Thread Diameter:0.3735 Inches Minimum And 0.3745 Inches MaximumGrip Length:0.375 Inches Minimum And 0.198 Inches MaximumHole Quantity:3Hole Quantity:10000 Pounds Per Square InchHond Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchHole Configuration Style:Hexagon CornersHole Configuration Style:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Spec 5th Sp | Width Between Flats: | 0.553 Inches Minimum And 0.564 Inches Maximum |
| Nominal Thread Diameter:0.375 InchesGrip Length:0.178 Inches Minimum And 0.198 Inches MaximumHole Quantity:3Hole Type:DrilledThread Quantity Per Inch:2Minimum Tensile Strength:16000 Pounds Per Square InchHole Configuration Style:8.0.00 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersMaterial:Stel Comp 4140 Overall Or Stel Comp E4340 Overall Or Stel Comp 6150 Overall Or Stel Comp 8735 Overall Or Stel Comp 8735 Overall Or Mil-s-6028 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil Spec 4th Material Response Overall Or Mil-s-6039 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Or-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Or Mil-s-6049 Mil Spec Sth Material Response OverallThread Series Designator:Unf | Hole Diameter: | 0.070 Inches Nominal |
| Grip Length:0.178 Inches Minimum And 0.198 Inches MaximumHole Quantity:3Hole Type:DrilledThread Quantity Per Inch:246000 Pounds Per Square InchMinimum Tensile Strength:60000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersMaterial:Keel Comp 1440 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qr.p-416,type 2,class 3 Fed Spec Single Treatment Response OverallMaterial Response Treatment Document And Classification:Qr.p-416,type 2,class 3 Fed Spec Single Treatment Response OverallMarce Treatment Document And Classification:Qr.p-416,type 2,class 3 Fed Spec Single Treatment Response OverallMarce Treatment Document And Classification:Unf | Grip Diameter: | 0.3735 Inches Minimum And 0.3745 Inches Maximum |
| Hole Quantity3Hole QuantityDrilledHole Type:DrilledThread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qu-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallThread Series Designator:Unf | Nominal Thread Diameter: | 0.375 Inches |
| Hole Type:DrilledThread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallSurface Treatment Document And Classification:Unf | Grip Length: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Thread Quantity Per Inch:24Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallQu-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallUnf | Hole Quantity: | 3 |
| Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallQrep-416,type 2,class 3 Fed Spec Single Treatment Response OverallOverallThread Series Designator:Unf | Hole Type: | Drilled |
| Hardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHole Configuration Style:Hexagon CornersMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:q-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallDurface Treatment Document And Classification:Unf | Thread Quantity Per Inch: | 24 |
| Hole Configuration Style:Hexagon CornersMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallUnfUnf | Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Classification:Surface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallThread Series Designator:Unf | Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Material:OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment Document And Classification:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Overall And Chromate OverallDifUnf | Hole Configuration Style: | Hexagon Corners |
| Classification:Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallThread Series Designator:Unf | Material: | |
| Surface Treatment Document And Classification:Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response OverallThread Series Designator:Unf | | |
| Classification: Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf | Surface Treatment: | Cadmium Overall And Chromate Overall |
| , second s | | Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: 80205-nas1306 Professional/industrial Association Standard | Thread Series Designator: | Unf |
| | Specification/standard Data: | 80205-nas1306 Professional/industrial Association Standard |

How to Order

Order this machine bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/NAS1306-3</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.