

## P/N NAS1306-31

### **Description**

Fastener Length: 2-33/64", Thread: 3/8-24, Thread Length: 9/16", NAS1306 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS130631

Minimum Qty (MOQ): 5

NSN: 5306-00-954-9038

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1306-31 Specifications

| Thread Class:                                  | 3a  |
|--|---|
| Thread Direction:                              | Right-hand  |
| Thread Length:                                 | 0.578 Inches Minimum  |
| Fastener Length:                               | 2.516 Inches Nominal  |
| Head Style:                                    | Dished Hexagon  |
| Head Height:                                   | 0.188 Inches Nominal  |
| Width Between Flats:                           | 0.553 Inches Minimum And 0.564 Inches Maximum   |
| Grip Diameter:                                 | 0.3735 Inches Minimum And 0.3745 Inches Maximum   |
| Nominal Thread Diameter:                       | 0.375 Inches  |
| Grip Length:                                   | 1.938 Inches Nominal  |
| Thread Quantity Per Inch:                      | 24  |
| Minimum Tensile Strength:                      | 160000 Pounds Per Square Inch   |
| Hardness Rating:                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall   |
| Material:                                      | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall  |
| Material Document And Classification:          | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall |
| Surface Treatment:                             | Cadmium Overall And Chromate Overall  |
| Surface Treatment Document And Classification: | Qq-p-416 Ty2,cl 2 Fed Spec Single Treatment Response Overall  |
| Thread Series Designator:                      | Unf   |
| Specification/standard Data:                   | 80205-nas1306 Professional/industrial Association Standard  |
|  |   |

## **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1306-31">https://military-fasteners.com/bolts/machine+bolts/NAS1306-31</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1306-31">https://military-fasteners.com/bolts/machine+bolts/NAS1306-31</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1306-31">https://military-fasteners.com/bolts/machine+bolts/NAS1306-31</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1306-31">https://military-fasteners.com/bolts/machine+bolts/NAS1306-31</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS1306-31">https://military-fasteners.com/bolts/machine+bolts/NAS1306-31</a> and selecting the quantity you want the complete your order.