

Description

Fastener Length: 3-53/64", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS130652DH |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-437-4278 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1306-52DH Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Length: | 0.553 Inches Minimum And 0.603 Inches Maximum |
| Fastener Length: | 3.813 Inches Minimum And 3.843 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.188 Inches Minimum And 0.203 Inches Maximum |
| Width Between Flats: | 0.553 Inches Minimum And 0.564 Inches Maximum |
| Hole Diameter: | 0.070 Inches Nominal |
| Grip Diameter: | 0.3735 Inches Minimum And 0.3745 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.375 Inches |
| Hole Quantity: | 3 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Hexagon Corners |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 3.606 Inches Minimum First Hole And 3.656 Inches Maximum First Hole |
| Material: | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty2 Cl2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS1306-52DH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.