

# P/N NAS1306-5H

Military-Fasteners.com

#### Description

Fastener Length: 57/64", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 19/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | NAS13065H                                 |
|-------------------------|---|
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5306-00-047-3553                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS1306-5H Specifications

| Thread Class:                                     | 3a   |
|---|--|
| Thread Direction:                                 |  |
|   | Right-hand   |
| Thread Length:                                    | 0.553 Inches Minimum And 0.603 Inches Maximum  |
| Fastener Length:                                  | 0.875 Inches Minimum And 0.905 Inches Maximum  |
| Head Style:                                       | Dished Hexagon   |
| Head Height:                                      | 0.188 Inches Minimum And 0.203 Inches Maximum  |
| Width Between Flats:                              | 0.553 Inches Minimum And 0.564 Inches Maximum  |
| Hole Diameter:                                    | 0.070 Inches Nominal   |
| Grip Diameter:                                    | 0.3735 Inches Minimum And 0.3745 Inches Maximum  |
| Nominal Thread Diameter:                          | 0.375 Inches   |
| Grip Length:                                      | 0.302 Inches Minimum And 0.322 Inches Maximum  |
| Hole Quantity:                                    | 3  |
| Hole Type:  | Drilled  |
| Thread Quantity Per Inch:                         | 24   |
| Minimum Tensile Strength:                         | 160000 Pounds Per Square Inch  |
| Hole Configuration Style:                         | Hexagon Corners  |
| Material:   | Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740<br>Overall  |
| Material Document And<br>Classification:          | Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd<br>Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall |
| Surface Treatment:                                | Cadmium Overall  |
| Surface Treatment Document And<br>Classification: | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall  |
| Thread Series Designator:                         | Unjf   |
| Specification/standard Data:                      | 80205-nas1306 Professional/industrial Association Standard   |

## How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/NAS1306-5H</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.