

Description

Fastener Length: 1-13/32", Thread: 7/16-20, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS130713
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-459-0850
National Motor Freight:	093470, Bolts / Nuts I / S

NO IMAGE
AVAILABLE

P/N NAS1307-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.594 Inches Minimum
Fastener Length:	1.391 Inches Minimum And 1.421 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.219 Inches Nominal
Width Between Flats:	0.679 Inches Minimum And 0.690 Inches Maximum
Grip Diameter:	0.4354 Inches Minimum And 0.4360 Inches Maximum
Nominal Thread Diameter:	0.4375 Inches
Grip Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall And Steel Comp E4340 Overall And Steel Comp 6150 Overall And Steel Comp 8735 Overall And Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall And Mil-s-5000 Mil Spec 2nd Material Response Overall And Mil-s-8503 Mil Spec 3rd Material Response Overall And Mil-s-6098 Mil Spec 4th Material Response Overall And Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2.cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1307 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1307-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.