

**Description**


Fastener Length: 2-3/32", Thread: 7/16-20, Thread Length: 19/32",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS130724
Minimum Qty (MOQ):	10
NSN:	5306-01-311-6242
ECCN:	EAR99



## P/N NAS1307-24 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.594 Inches Minimum
<b>Fastener Length:</b>	2.094 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.219 Inches Nominal
<b>Width Between Flats:</b>	0.679 Inches Minimum And 0.690 Inches Maximum
<b>Grip Diameter:</b>	0.4360 Inches Minimum And 0.4370 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.438 Inches
<b>Grip Length:</b>	1.500 Inches Nominal
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1307-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.