

Description

Fastener Length: 2-15/64", Thread: 3/8-20, Thread Length: 19/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS130726D
Minimum Qty (MOQ):	10
NSN:	5306-01-570-7381
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS1307-26D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.594 Inches Nominal
Fastener Length:	2.204 Inches Minimum And 2.234 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.219 Inches Minimum And 0.234 Inches Maximum
Width Between Flats:	0.679 Inches Minimum And 0.690 Inches Maximum
Grip Diameter:	0.436 Inches Minimum And 0.437 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
Nominal Thread Diameter:	0.437 Inches
Grip Length:	1.615 Inches Minimum And 1.635 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.018 Inches Nominal First Hole
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Ams 6415 Assn Std 1st Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1307-26D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.