

Description

Fastener Length: 7/8", Hole Diameter: 1/16", Thread: 7/16-20, Thread Length: 19/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS13075H
Minimum Qty (MOQ):	5
NSN:	5306-00-063-7683
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1307-5H Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.594 Inches Minimum
Fastener Length:	0.906 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.219 Inches Nominal
Width Between Flats:	0.679 Inches Minimum And 0.690 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Nominal Thread Diameter:	0.438 Inches
Grip Length:	0.312 Inches Nominal
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Corners
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1307 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1307-5H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.