

Description

Fastener Length: 1-1/8", Thread: 7/16-20, Thread Length: 19/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS13079
Minimum Qty (MOQ):	10
NSN:	5306-00-054-9373
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NAS1307-9



P/N NAS1307-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.594 Inches Minimum
Fastener Length:	1.156 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.219 Inches Nominal
Width Between Flats:	0.679 Inches Minimum And 0.690 Inches Maximum
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Nominal Thread Diameter:	0.438 Inches
Grip Length:	0.562 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1307 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1307-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.