

**Description**

Fastener Length: 3-63/64", Thread: 1/2-20, Thread Length: 3/4

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS130852D
Minimum Qty (MOQ):	1
NSN:	5306-01-021-2696
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1308-52D Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.710 Inches Minimum And 0.760 Inches Maximum
<b>Fastener Length:</b>	3.970 Inches Minimum And 4.000 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Diameter:</b>	0.250 Inches Minimum And 0.265 Inches Maximum
<b>Head Height:</b>	0.250 Inches Minimum And 0.265 Inches Maximum
<b>Width Between Flats:</b>	0.741 Inches Minimum And 0.752 Inches Maximum
<b>Grip Diameter:</b>	0.4985 Inches Minimum And 0.4995 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Grip Length:</b>	3.240 Inches Minimum And 3.260 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	3.744 Inches Minimum First Hole And 3.794 Inches Maximum First Hole
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas1308 Professional/Industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1308-52D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.