

Description

Fastener Length: 4-47/64", Thread: 1/2-20, Thread Length: 47/64", NAS1308 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS130864
Minimum Qty (MOQ):	2
NSN:	5306-00-851-2609
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS1308-64 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.735 Inches Minimum
Fastener Length:	4.735 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.250 Inches Nominal
Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Grip Diameter:	0.4985 Inches Minimum And 0.4995 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	4.000 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1308 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1308-64> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.