

Description

Fastener Length: 4-11/32", Thread: 1/2-18, Thread Length: 13/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS130956

Minimum Qty (MOQ): 5

NSN: 5306-01-011-0619

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9



P/N NAS1309-56 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.840 Inches Nominal
Fastener Length:	4.325 Inches Minimum And 4.355 Inches Maximum
Head Style:	Hexagon
Head Height:	0.288 Inches Nominal
Width Between Flats:	0.865 Inches Minimum And 0.877 Inches Maximum
Nominal Thread Diameter:	0.562 Inches
Grip Length:	3.490 Inches Minimum And 3.510 Inches Maximum
Features Provided:	Unfinished Head
Thread Quantity Per Inch:	18
Material:	Steel Overall
Material Document And Classification:	Mil-b-7838 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1309 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1309-56> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.