

**Description**

Fastener Length: 4-11/32", Thread: 1/2-18, Thread Length: 13/16",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS130956
Minimum Qty (MOQ):	5
NSN:	5306-01-011-0619
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



\* See page 2 for technical characteristics

## P/N NAS1309-56 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.840 Inches Nominal
<b>Fastener Length:</b>	4.325 Inches Minimum And 4.355 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.288 Inches Nominal
<b>Width Between Flats:</b>	0.865 Inches Minimum And 0.877 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.562 Inches
<b>Grip Length:</b>	3.490 Inches Minimum And 3.510 Inches Maximum
<b>Features Provided:</b>	Unfinished Head
<b>Thread Quantity Per Inch:</b>	18
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Mil-b-7838 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type 2 Cl 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf
<b>Specification/standard Data:</b>	80205-nas1309 Professional/Industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS1309-56> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.