

Description

grip range: 0.010" - 0.060", thread: 4-40, blind rivet nut, flat head, aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS27130A1](#)

SKU / Model:

NAS1329A0460

Minimum Qty (MOQ):

25

NSN:

5310-00-639-7610

ECCN:

EAR99

National Motor Freight:

013540, Alum Nuts



P/N NAS1329A04-60 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat |
| Head Diameter: | 0.255 Inches Minimum And 0.285 Inches Maximum |
| Head Height: | 0.025 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.151 Inches Minimum And 0.155 Inches Maximum |
| Nut Length: | 0.370 Inches Nominal |
| Err Default: | +0.010/+0.060 Inches |
| Unable To Decode: | +0.010 To 0.060 Inches |
| Shank End Type: | Open |
| Thread Series: | Unc |
| Thread Quantity Per Inch: | 40 |
| Nominal Thread Size: | 0.112 Inches |
| Material: | Aluminum Alloy 6053 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1329 Professional/industrial Association Standard |

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A04-60> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.