

Description

Thread Size: 1/8", Nut Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1329A0485
Minimum Qty (MOQ):	10
NSN:	5310-00-724-3879
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N NAS1329A04-85 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat
Head Diameter:	0.255 Inches Minimum And 0.285 Inches Maximum
Head Height:	0.025 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.151 Inches Minimum And 0.155 Inches Maximum
Nut Length:	0.355 Inches Minimum And 0.385 Inches Maximum
Err Default:	+0.060/+0.085 Inches
Unable To Decode:	+0.060 To 0.085 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	40
Nominal Thread Size:	0.112 Inches
Material:	Aluminum Alloy 6053 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

How to Order

Order this blind rivet plain nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A04-85> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.