

Description

Thread Size: 1/8", Nut Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------|
| SKU / Model: | NAS1329A0485 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-00-724-3879 |
| National Motor Freight: | 013540, Alum Nuts |

NO IMAGE
AVAILABLE

P/N NAS1329A04-85 Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Head Style: | Flat |
| Head Diameter: | 0.255 Inches Minimum And 0.285 Inches Maximum |
| Head Height: | 0.025 Inches Nominal |
| Nut Style: | Blind Rivet W/smooth Round Shank |
| Nut Diameter: | 0.151 Inches Minimum And 0.155 Inches Maximum |
| Nut Length: | 0.355 Inches Minimum And 0.385 Inches Maximum |
| Err Default: | +0.060/+0.085 Inches |
| Unable To Decode: | +0.060 To 0.085 Inches |
| Shank End Type: | Open |
| Thread Series: | Unc |
| Thread Quantity Per Inch: | 40 |
| Nominal Thread Size: | 0.112 Inches |
| Material: | Aluminum Alloy 6053 Overall |
| Material Document And Classification: | Qq-a-430 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas1329 Professional/industrial Association Standard |

How to Order

Order this blind rivet plain nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A04-85> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.