



★ FASTENERS

Military-Fasteners.com

P/N NAS1329A04K60

Description

Aluminum rivet nut, thread: 4-40

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1329A04K60
Minimum Qty (MOQ):	25
NSN:	5310-00-456-6897
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1329A04K60 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.255 Inches Minimum And 0.285 Inches Maximum
Key Length:	0.023 Inches Maximum
Head Height:	0.025 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.151 Inches Minimum And 0.155 Inches Maximum
Nut Length:	0.330 Inches Minimum And 0.360 Inches Maximum
Err Default:	+0.010/+0.060 Inches
Unable To Decode:	+0.010 To 0.060 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	40
Nominal Thread Size:	0.112 Inches
Material:	Aluminum Alloy 6053 Overall
Material Document And Classification:	Mil-r-1150 Mil Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Type 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas329 Professional/Industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A04K60> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.