

**Description**

Aluminum rivet nut, thread: 4-40

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1329A04K60
Minimum Qty (MOQ):	25
NSN:	5310-00-456-6897
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS1329A04K60 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Keyed
<b>Head Diameter:</b>	0.255 Inches Minimum And 0.285 Inches Maximum
<b>Key Length:</b>	0.023 Inches Maximum
<b>Head Height:</b>	0.025 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.151 Inches Minimum And 0.155 Inches Maximum
<b>Nut Length:</b>	0.330 Inches Minimum And 0.360 Inches Maximum
<b>Err Default:</b>	+0.010/+0.060 Inches
<b>Unable To Decode:</b>	+0.010 To 0.060 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unc
<b>Thread Quantity Per Inch:</b>	40
<b>Nominal Thread Size:</b>	0.112 Inches
<b>Material:</b>	Aluminum Alloy 6053 Overall
<b>Material Document And Classification:</b>	Mil-r-1150 Mil Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Type 2 Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas329 Professional/industrial Association Standard

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A04K60> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.