

Description

Thread Size: 1/8", Nut Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1329A06B75
Minimum Qty (MOQ):	5 EA
NSN:	5310-00-188-7983
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N NAS1329A06B75 Specifications

Thread Class:	2b
Thread Direction:	Right-hand
Head Style:	Flat
Head Diameter:	0.310 Inches Minimum And 0.340 Inches Maximum
Head Height:	0.032 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.185 Inches Minimum And 0.189 Inches Maximum
Nut Length:	0.610 Inches Minimum And 0.640 Inches Maximum
Err Default:	+0.010/+0.075 Inches
Unable To Decode:	+0.010 To 0.075 Inches
Shank End Type:	Closed
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Material:	Aluminum Alloy 6053 Overall
Material Document And Classification:	T4 Assn Std Single Material Response Overall
Surface Treatment:	Anodize Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1329A06B75> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.