

Description

Thread Size: 1/8", Nut Length: 1/2",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[MS27130A8K A6K120](#)

SKU / Model:	NAS1329A06K120
Minimum Qty (MOQ):	50
NSN:	5310-00-188-7948
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N NAS1329A06K120 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat Keyed
Head Diameter:	0.310 Inches Minimum And 0.340 Inches Maximum
Key Length:	0.055 Inches Nominal
Head Height:	0.032 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.185 Inches Minimum And 0.189 Inches Maximum
Nut Length:	0.485 Inches Minimum And 0.515 Inches Maximum
Err Default:	+0.075/+0.120 Inches
Unable To Decode:	+0.075 To 0.120 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.138 Inches
Material:	Aluminum Alloy 6053 Overall
Material Document And Classification:	Qq-a-430,temper T4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/Industrial Association Standard

How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A06K120> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.