

**Description**

grip range: 0.12" - 0.16", thread: 6-32, keyed, rivnut, flat head, aluminum alloy

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information****Alternate Part Numbers**

[MS27130A9K](#)

SKU / Model:	NAS1329A06K160
Minimum Qty (MOQ):	50
NSN:	5310-00-787-3773
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



## P/N NAS1329A06K160 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Keyed
<b>Head Diameter:</b>	0.310 Inches Minimum And 0.340 Inches Maximum
<b>Key Length:</b>	0.055 Inches Nominal
<b>Head Height:</b>	0.032 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.185 Inches Minimum And 0.189 Inches Maximum
<b>Nut Length:</b>	0.485 Inches Minimum And 0.515 Inches Maximum
<b>Err Default:</b>	+0.120/+0.160 Inches
<b>Unable To Decode:</b>	+0.120 To 0.160 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unc
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.138 Inches
<b>Material:</b>	Aluminum Alloy 6061 Overall
<b>Material Document And Classification:</b>	Qq-a-430,t4 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A06K160> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.