

Description

Thread Size: 1/8", Nut Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1329A08240
Minimum Qty (MOQ):	10 EA
NSN:	5310-00-952-3471
Schedule B:	7616.10.3000
ECCN:	9A991
National Motor Freight:	013540, Alum Nuts



* See page 2 for technical characteristics

P/N NAS1329A08-240 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Head Style:	Flat
Head Diameter:	0.342 Inches Minimum And 0.372 Inches Maximum
Head Height:	0.032 Inches Nominal
Nut Style:	Blind Rivet W/smooth Round Shank
Nut Diameter:	0.217 Inches Minimum And 0.221 Inches Maximum
Nut Length:	0.610 Inches Minimum And 0.640 Inches Maximum
Err Default:	+0.200/+0.240 Inches
Shank End Type:	Open
Thread Series:	Unc
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.164 Inches
Material:	Aluminum Alloy 3003 Overall Or Aluminum Alloy 6053 Overall Or Aluminum Alloy 6061 Overall
Material Document And Classification:	Mil-r-1150 Mil Spec All Material Responses Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1329 Professional/industrial Association Standard

How to Order

Order this rivnut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A08-240> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.