

## Description

keyed grip range: 0.010" - 0.075", thread: 8-32, blind rivet, flat head, aluminum alloy, NAS1329 series nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS1329A08K75
Minimum Qty (MOQ):	100
NSN:	5310-00-188-7969
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	013540, Alum Nuts



\* See page 2 for technical characteristics

## P/N NAS1329A08K75 Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Head Style:</b>	Flat Keyed
<b>Head Diameter:</b>	0.342 Inches Minimum And 0.372 Inches Maximum
<b>Key Length:</b>	0.055 Inches Maximum
<b>Head Height:</b>	0.032 Inches Nominal
<b>Nut Style:</b>	Blind Rivet W/smooth Round Shank
<b>Nut Diameter:</b>	0.217 Inches Minimum And 0.221 Inches Maximum
<b>Nut Length:</b>	0.423 Inches Minimum And 0.453 Inches Maximum
<b>Err Default:</b>	+0.010/+0.075 Inches
<b>Unable To Decode:</b>	+0.010 To 0.075 Inches
<b>Shank End Type:</b>	Open
<b>Thread Series:</b>	Unc
<b>Thread Quantity Per Inch:</b>	32
<b>Nominal Thread Size:</b>	0.164 Inches
<b>Material:</b>	Aluminum Alloy 6053 Overall
<b>Material Document And Classification:</b>	Qq-a-430,t4 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1329 Professional/industrial Association Standard

## How to Order

Order this blind rivet plain nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A08K75> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.