

**Description**

Thread: 10-32, Thread Size: 1/4", Nut Length: 5/8", rivnut

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[AEA10K140](#)

|                         |                   |
|-------------------------|-------------------|
| SKU / Model:            | NAS1329A3130      |
| Minimum Qty (MOQ):      | 50                |
| NSN:                    | 5310-00-141-3062  |
| Schedule B:             | 7616.10.1000      |
| ECCN:                   | EAR99             |
| National Motor Freight: | 013540, Alum Nuts |



\* See page 2 for technical characteristics

## P/N NAS1329A3-130 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3b   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Head Style:</b>                                    | Flat   |
| <b>Head Diameter:</b>                                 | 0.391 Inches Minimum And 0.421 Inches Maximum              |
| <b>Head Height:</b>                                   | 0.038 Inches Nominal                                       |
| <b>Nut Style:</b>                                     | Blind Rivet W/smooth Round Shank                           |
| <b>Nut Diameter:</b>                                  | 0.246 Inches Minimum And 0.250 Inches Maximum              |
| <b>Nut Length:</b>                                    | 0.579 Inches Minimum And 0.609 Inches Maximum              |
| <b>Err Default:</b>                                   | +0.080/+0.130 Inches                                       |
| <b>Unable To Decode:</b>                              | +0.080 To 0.130 Inches                                     |
| <b>Shank End Type:</b>                                | Open   |
| <b>lii End Item Identification:</b>                   | Mrap - Cougar  |
| <b>Thread Series:</b>                                 | Unf  |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Nominal Thread Size:</b>                           | 0.190 Inches   |
| <b>Material:</b>                                      | Aluminum Alloy 6053 Overall                                |
| <b>Material Document And Classification:</b>          | Qq-a-430,t4 Fed Spec Single Material Response Overall      |
| <b>Surface Treatment:</b>                             | Anodize Overall  |
| <b>Surface Treatment Document And Classification:</b> | Mil-a-8625,ty 2 Mil Spec Single Treatment Response Overall |

## How to Order

Order this plain blind rivet nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+blind+rivet+nuts/NAS1329A3-130> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.